

Commercial, Small Size, Power Saving, Clear Voice



RT-4410

Professional Digital Radio

- Support Digital /Analog Modes
- Call Digital Encryption
- Multi-call Modes



RT-4410

Professional Digital Radio

Main Functions

- Support Digital / Analog Modes
- Multi-call Modes: Individual Call, Group Call, All Call, Emergency Call
- Emergency Alarm: Local and Remote Alarm
- Call Digital Encryption
- Scan Function
- Whisper Function
- Wide/Narrow Band Compatible
- Remote Kill and Revive Function
- CTCSS / DCS Encoding and Decoding
- SMS Function
- LCD Display, Easier for Operation

General Specifications

Frequency Range	136-174MHz; 400-470MHz
Channel Capacity	256
Channel Spacing	12.5kHz \ 25kHz
Normal Operating Voltage	DC3.7V ± 15%
Battery Pack	1650mAh(Li-ion)
Operating Temperature	-20°C ~ +60°C
RF Power	2W \ 1W
4FSK Modulation Accuracy	≤5% @ 25°C, ≤10% @ Extreme Temperature
Adjacent Channel Power Ratio	≥ 65dB(Wide Band), ≥ 55dB(Narrow Band)
Analog Receiving Sensitivity	-121dBm
Digital Receiving Sensitivity	-117dBm(BER≤1%)
Audio Power	≥450mW(8Ω)
Dimensions(W × H × D)	52 × 115 × 34mm
Weight	181g(With Battery and Antenna)

Standard Accessories



Trackstar Communications, Inc.
Office: 404-916-3264-Office Fax: 404-601-4599
Email: info@trackstarcommunications.com
Website: www.trackstarcommunications.com